



SMARTRUCK

smart...for a reason

HD

P/N: C17DASHAI
AI Enabled DashCam

Product Specification - The **SmarTruck HD C17DASHAI** (AI-enabled) Dash Cam with WIFI captures everything that is happening inside and outside the vehicle, which you can view from mobile app or management platform anytime. The Advanced Driving Assistance System of C17DASHAI can help you avoid collisions and accidents by offering alerts to potential problems. Driver Monitoring System corrects risky behaviors such as phone use, smoking, fatigue driving and inattentive driving in real time before accidents happen. Improve safety, protect your fleet with the SmarTruck HD C17DASHAI - AI enabled Dash Cam.



Camera BRV CRD-04 / CA060 / Superseded by C17DASHAI

Click on the QR Code to download this literature



Camera Specs	
Part No.	C17DASHAI
Size / weight / color	L143mm*H46mm*ø38mm / 120g / black
Camera sensor	2Mega CMOS image
Lens Angle	6G (H: 175°H: 150°, V: 90°)
Two cameras	Support/1080P/H150°, C/720P/H150°
WIFI	Built-in WIFI module (IEEE 802.11b/g/n)
Video	Normal recording - Parking guard (parking guard is on, the vehicle vibration after flameout)
Sound recording	Built-in Microphone
Audio and video format	Video: H.264/H.265°MP4 forma Audio: AAC
Storage media	TF high-speed memory card (maximum support 256G, make sure to CLASS10 and above original genuine card)
Speaker	Built-in speaker
Button	Power button; Reset button; Upgrade button (press the key to enter the upgrade mode)
LED	2 LED (red - blue)
G-Sensor	Built-in triaxial three-dimensional collision acceleration sensor
GPS	Support GPS/GLONASS
RTC	Time synchronized automatically when connect to the internet or GPS.
Parking guard	The recorder uses car power and turns on the parking guardthe ignition started, It will start the video automatically when vibration caused
Video output	HDMI
Language settings	English, Simplified Chinese, Traditional Chinese, etc.
Photos	Support JPG format photo capture
Resolution/Frame rate	1920x1080@30fps
Loop recording	Time 1, 2, 3 minutes optional
Upgrade interface	SD card upgrade (press the upgrade button enter the upgrade)
Communication Interface	Reserved UART / IR interface
HDMI interface	Reserved HDMI interface
Alarm I/O	Define input / output alarm line (active low)
Lock	With lock to protect card, tamper resistant
Power	9V-32V car battery
Power consumption	7W(Max)
Standby current	Less than 10mA
Operating temperature	-40 ° C to + 75° C
Storage temperature	-40 ° C to + 90° C

Product specifications subject to change on 60-day notice.