



## **Product Specification**

The high-performance **SmarTruck HD** Part No C2B124 flushmount high-performance camera is equipped with a high-resolution 1/3" CMOS imaging sensor that delivers a 700 TV lines resolution and a wide 120° diagonal field-of-view. MORE INFORMATION IS NEEDED HERE.





Camera Specs	NEED SPECS
Part No.	C2B124
Image Device	1/3" CMOS
TV System	NTSC/PAL
Effective Pixels	976(H) x 592(V)
Sensing Area	4.880mm*3.670mm
Sync System	Internal
Resolution	700 TVL
Minimum Illumination	0.1 Lux (day) 0.0 Lux (night)
Microphone	No
IR LED Qty	18PCS
Video Output	1.0 Vp-p/75 Ohm
Scanning System	Interlace
AGC	Auto
Signal to noise ratio	Better than 48dB
White balance	Auto
Gamma Consumption	0.45
Electronic Shutter	Auto
Backlight Compensation	Auto
Power Supply	DC12V
Lens	2.8mm
Lens Angle	120° Diagonal
Current Drain	65±5mA
Operating Temperature	'-20°C~70°C, RH 95% MAX
Storage Temperature	'-30°C~80°C, RH 95% MAX
Storage Temperature	'-30°C~80°C, RH 95% MAX

**Camera Features Need specs** 

- High Resolution Sensor 1/3" (CMOS) Complementary Metal–Oxide–Semiconductor
- 120° Diagonal Field of View
- Metal Die-Cast Housing
- Electronic Auto Iris Control
- 18 Infra-Red (IR) Light Emitting Diodes (LED)
- Auto White Balance
- Back-Light Compensation (BLC)
- Vibration Rating = 10G
- "T" Slot-Adjustable Monitor Mount
- 18 Extra-Brite (NIR) Light-Emitting Diodes (LED)

Camera CA009 / RVHD-CC25 / Superseded by C2B124

Product specifications subject to change on 60-day notice.

