



SMARTRUCK HD

P/N: C2F134
130° FOV Color Camera (4P)

Product Specification - The high-performance **SmarTruck HD** Part No C2F134 camera delivers a sharp wide-angle image to the driver and provides outstanding visibility. Five (5 high intensity) infra-red LED's are twice as powerful as most cameras on the market. The IP69K water-intrusion rating means it is waterproof under severe conditions. It has a thermostatically controlled heater and may be pressure washed and steam cleaned. The camera includes stainless bracket and mounting hardware.



Camera Features

- High-Res L 640TV Lines
- Lens 2.45mm
- 1/2.9" SONY CMOS Image Sensor
- D-WDR(Wide Dynamic range)
- LED Auto On/Off CDS Sensor
- True Day & Night (IR filter changeable)
- Waterproof (IP69K)
- 5 x Infrared LED & 1 x CDS Sensor
- Built-in Microphone.
- Normal & Mirror
- Auto-Heating (optional)
- Die-Cast Aluminum Housing

Camera CA014 / RVHD-CC77130B / Superseded by C2F134

Product specifications subject to change on 60-day notice.

Part No	C2F134
Image Sensor	1/3" Sony Super HAD Color CCD
Total Pixels	2000(H) X 1121(V)
Number of effective pixels	1984(H) X 1105(V)
Video Signal System	NTSC: 410K, PAL: 470K
Visual Resolution	640TVL
Video Output	CVBS, Composite 1.0Vp-p / 75 ohm
S/N Ratio	More than 48 dB
Min. Illumination	0 Lux (With IR LED)
Lens	2.45mm
Function	Mechanical Day & Night (IR filter changeable) Audio , Normal & mirror , Auto-Heating
Power Input range	DC12V~30V
Power Consumption (DC 12V)	3.5Watt / Heater & IR ON (290mA) , IR OFF Max (90mA)
Operating Temp	-30°C ~ +85°C
Storage Temp	-40°C ~ +85°C
Size	69(W) x 42(H) x 57(D)/mm
Weight	Approx. 0.37Kg
Housing Color	Black
LED Angle	850Nano IR LED * 5pcs 90°
Logo	SmarTruckHD
Connector	4P Screw
Bracket Mounting Hole	6.5mm(SUS)

Click on the QR Code to download this literature

