

## P/N: M1074RV

7.2" Rearview Mirror Monitor with Full Display Screen

SERIES 500

**Product Specification - The SmarTruck HD Part No M1074RV** Premium 7.2" Rearview Mirror Monitor offers a high transparent 7.2-inch 16:9 LCD widescreen broad view that enables you to monitor critical blind-spots around the vehicle while driving. The M1074RV supports four HD or CVBS Cameras and will automatically switch rear camera when activated when the vehicle is in reverse or a side camera activated by a turn-signal trigger.



This SmarTruck HD monitor provides a broad view of critical blind-spots around the vehicle while driving.



## **Monitor Features**

- Support 4CH x 1080P or 720P cameras
- Video input:1 x VGA, 1 x DVD
- System format: 720P, 1080P, NTSC/PAL
- · Multiple camera image display mode
- Trigger priority
- Auto scan, scan channel and time can be set according to the users' demand
- Touch screen available, can recognize left and right side "swipe" to realize channel switching
- Support level 60 LCD manual backlight adjustment, level 60 automatic adjustment

• Contrast: 600:1

Resolution: 1024\*600Brightness: 600cd/m2

• Power consumption: MAX.25W

• DC: 10-32V

Monitor MT013 / RVHD-IMM73R / Superseded by M1074RV

Product specifications subject to change on 60-day notice.

| Part No.          | M1074RV                             |
|-------------------|-------------------------------------|
| Monitor           | 7.2" Wide LCD Display Monitor       |
| CPU               | TW8836                              |
| LCD Display       | 7.2 inch 1280*400 Resolution        |
| Input             | 4 camera input                      |
| Camera Connector  | 6Pminidin                           |
| Auto Trigger      | 3 Camera trigger wires. Auto Switch |
| Image             | 16:09                               |
| Color system      | RGB , AHD or CVBS                   |
| Resolution        | 7.2 inch 1280*400 Resolution        |
| Luminance         | 800±100cd/m <sup>2</sup>            |
| Power requirement | DC 9V~16V                           |
| Operating Current | 495±15MA(DC13±0.1V)                 |
| Operating temp    | -20° to +70°, RH 90%                |
| Storage temp      | -40° to +80°, RH 90%                |
| Certificate       | CE,EMC,FCC,ISO9001:2008,E8          |

Click on the QR Code to download this literature

