



SMARTRUCK

smart...for a reason

HD

P/N: M675Q

7" QUAD Color Monitor w/DVR

SERIES 600

Product Specification - The SmarTruck HD Part No M675Q - This 7" TFT Active Matrix color monitor comes complete with built-in DVR with an optional SD card and is designed to support up to four cameras. It also supports four audio inputs to allow for audio capture. This monitor supports NTSC, PAL and SECAM formats and is protected by our Standard Extended-Duty 5-Year Warranty.



Monitor Features

- High Resolution Crystal Clear Display
- Advanced OSD Menu for easy navigation
- Supports up to 4 Cameras w/ waterproof connectors
- Extra RCA input for multimedia while parking (GPS, External DVD)
- Provides 1 Video / 1 Audio Signal Output
- Supports Single / Dual / Triple / QUAD viewing options
- OSD Control for Individual Normal/Mirror Camera Image
- Auto power on when making back / left / right / front turn
- Support 10V ~ 36V DC Power Supply
- Auto Detection for NTSC / PAL / SECAM System
- Dimmer Control
- Built-in DVR System (SD Card type)
- Professional Metal Case with Certified Anti-Shock Design up to 10G
- "Auto Sense Technology" adds and removes cameras for faster installation
- Motion Detection Surveillance while vehicle in idle mode
- Extra Shielded Cabling to prevent: Electrical, Engine, and RF Interference

Monitor MT036 / Superseded by M675Q

Product specifications subject to change on 60-day notice.

Monitor Part No.	M675Q
Description	7" Quad Color Monitor 16:9
Display Method	TFT Active Matrix System
Active Area	154.08 (W) * 87.05 (H) mm
Resolution (dot)	1440(H) * 234(V)= 336960 (dots)
Back Light	LED Type
Brightness	300cd/m ²
Contrast Ratio	400
View Angle Range (Left)	65 degree
View Angle Range (Right)	65 degree
View Angle Range (Top)	40 degree
View Angle Range (Down)	65 degree
Operation Temperature	(-20°C ~ +70°C)
Storage Temperature	(-30°C ~ +85°C)
Power Input Consumption	DC+ 10V ~ 36V <1500mA
Video System	NTSC / PAL / SECAM System
Video Input / Output	Composite video signal 1Vp-p 75Ω
Remote Control	IR Wireless OSD Remote Control
Touch Panel Control	X 1 OSD Touch Control (Option)
Dimmer Control	X 1 OFF / 1 ~ 9
Support Picture	X 4 Single / Dual / Triple / QUAD
AV Input	X 1 (RCA JACK)
AV Output	X 1 (RCA JACK)
SPK Output	X 1 (1W)
Camera Connector	6Pminidin
Camera Inputs	x4 Camera
DVR Input / Output	X 1 SD CARD (Option)
Overall Dimension	192mm x 140mm x 52mm
Weight	2200(g)
Safety	FCC / CE / E13

Click on the QR Code to download
this literature

