



SMARTRUCK
 HD
 smart...for a reason

P/N: C4F176HD-XL

**170° Degree Field-of-View FOV
 High Performance AHD Low
 Light Color Camera**

Product Specification - The high-performance **Part No C4F176HD-XL** camera delivers a sharp wide-angle image to the driver and provides outstanding visibility. Ten high intensity infra-red LED's are twice as powerful as most cameras on the market. (50 ft) This camera is IP69K rated which means it is waterproof under severe conditions. The camera includes stainless bracket and mounting hardware.



Camera with Sun Shield



Camera Features

- AHD 1080p @ 30fps
- Lens F2.2
- 1/2.9" SONY CMOS Image Sensor
- D-WDR (Wide Dynamic range)
- LED Auto On/Off CDS Sensor
- True Day & Night (IR filter changeable)
- Waterproof (IP69K)
- 10 x Infrared LED & 1 x CDS Sensor
- Built-in Microphone.
- Normal & Mirror
- Die-Cast Aluminum Housing

Product specifications subject to change on 60-day notice.

SmarTruck Part No	C4F176HD-XL
Image Sensor	1/2.9" SONY CMOS Image Sensor
Total Pixels	2000(H) X 1121(V)
Number of effective pixels	1984(H) X 1105(V)
Video Signal System	AHD 1080p @ 30fps
Visual Resolution	1080P
Video Output	AHD 2.0
S/N Ratio	50dB or more (AGC OFF)
Minimum Illumination	0 Lux (With IR LED)
Lens	F2.2
Function	Mechanical Day & Night (IR filter changeable) Audio, Normal & mirror
Power Input range	DC12V~ 30V
Power Consumption	2.8Watt / IR ON Max (230mA) , IR OFF Max (90mA)
Operating Temp	-30°C ~ +85°C
Storage Temp	-40°C ~ +85°C
Size	85(W) x 57.5(H) x 50(D)mm
Weight	Approx. 0.5Kg
Housing Color	Black
LED Angle	940Nano IR LED * 10pcs 60°
Logo	SmarTruck HD
Connector	6P Screw Lock
Bracket Mounting Hole	Standard. (Aluminum)

Click on the QR Code to download this literature

